



Axial Fans and Centrifugal Blowers

For industrial, process, marine and HVAC applications



Howden excels in configuring and customizing our products to meet a customer's specific application, whether a single unit or OEM serial production.

Howden covers the market segments of industrial, HVAC and Navy/DOD, marine and off-shore. We offer a global product catalog, ensuring the right product fit for your application.



Howden is a truly global company, with an established presence in more than 26 countries across every continent. Our network of local support services enables us to respond urgently to customer queries and maintenance requirements, and we understand the importance of local circumstances, from environmental legislation to energy costs.



Every product we deliver is backed by an unequivocal lifetime commitment to spare parts and product support. Replacement parts are made using the original production drawings, so that compatibility and quality are guaranteed. We also offer a full upgrade and enhancement program that allows customers to take advantage of new developments, or adapt existing equipment to changed conditions.

Revolving Around You[™]

Pressure and utility blowers

High flow:Up to 12,000 CFMHigh pressure:Up to 110" water gaugeClean air, particulate and material handling applications



AF cast aluminum pressure blowers

Volumes to 3,800 CFM

Pressures to 20" WG

Available in direct driven and belt driven configurations

Wheel types: Backward curved, forward curved and radial blade

Corrosion and spark resistant aluminum wheels

Light weight and rugged split cast aluminum field rotatable housings. Available with fabricated steel wheels and housing as option

Available in six basic fan sizes

Customized options available



Turbo pressure blowers

Volumes to 9,200 CFM Pressures to 86" WG Available in direct driven and belt driven configurations Wheel types: Backward curved and radial blade Continuously welded, heavy gauge housings Available in eight basic fan sizes Customized options available



RB pressure blowers

Volumes to 12,000 CFM
Pressures to 110" WG
Available in direct driven and belt driven configurations
Wheel type: Radial blade
Continuously welded, heavy gauge housings
Available in twenty-five basic fan sizes
Customized options available



SMB/SMD forward curved utility blowers

Volumes to 4,800 CFM
Pressures to 3" WG
Available in belt driven and direct driven configurations
Wheel type: Forward curved
Continuously welded, field rotatable housings
Packaged utility set
Available in six basic fan sizes
Customized options available



SC forward curved volume blowers

Volumes to 1,400 CFM
Pressures to 4" WG
Available in belt driven and direct driven configurations
Wheel type: Forward curved
Light weight and rugged split cast aluminum field rotatable housings
Available in four basic fan sizes
Customized options available

Backward-inclined fans

High flow:Up to 100,000 CFMHigh temperature:Up to 1000°FSWSI and DWDI configurations available

BCA, BCS backward-inclined fans, single width

Volumes to 100,000 CFM

Pressures to 25" WG

AMCA certified for air and sound performance

Available in belt driven and direct driven configurations

Wheel types: Backward curved and airfoil blade

Continuously welded, heavy gauge, field rotatable housings (Rotatable on fan sizes 122 thru 330 only)

Available in eighteen basic fan sizes

Customized options available



QBCA, QBCS backward-inclined fans, square housed

Volumes to 43,000 CFM

Pressures to 17" WG

AMCA certified for air and sound performance

Available in belt driven & direct driven configurations

Wheel types: Backward curved & airfoil blade

Compact continuously welded, heavy gauge, field rotatable square housings (Rotatable to four discharge positions)

Available in fourteen basic fan sizes

Customized options available



PBCA, PBCS backward-inclined plug fans

Volumes to 90,000 CFM	
Pressures to 12" WG	
Available in belt driven configuration or	nly
Wheel types: Backward curved & airfo	il blade
Continuously welded insulated plug for or low temperature applications	r high
Available with or without housing, inlet and venturi supports	venturi
Available in sixteen basic fan sizes and standard plug depths	l three
Customized options available	



DBCA, DBCS backward-inclined fans, double width

Volumes to 190,000 CFM
Pressures to 20" WG
Available in belt driven configuration only
Wheel types: Backward curved & airfoil blade
Continuously welded, heavy gauge, field rotatable housings (Rotatable on fan sizes 122 thru 330 only)
Available in sixteen basic fan sizes
Also available in DQBCA & DQBCS compact square design
Customized options available



Industrial exhausters

High flow: High pressure: Up to 40,000 CFM Up to 23" water gauge

Volumes to 40,000 CFM

Pressures to 23" WG

Available in belt driven and direct driven configurations

Wheel type: Radial blade

Continuously welded, heavy gauge, field rotatable and reversible housings (Rotatable, reversible on fan sizes 7 thru 21 only)

Air handling or severe duty material handling applications

Available in twelve basic fan sizes

Customized options available



PL plenum fans

High flow: High pressure: Up to 50,000 CFM Up to 10" water gauge

Volumes to 50,000 CFM

Pressures to 10" WG

Available in belt & direct driven configurations

Wheel type: Backward curved

Welded, heavy gauge, frame

Rugged, easily adjustable motor mount

Available in thirteen basic fan sizes

Customized options available



Axial fans

High flow: High pressure: Up to 425,000 CFM Up to 13" water gauge

JM aerofoil fans

Volumes to 425,000 CFM

Pressures to 10.5" WG

Available in both tube axial and vane axial designs AMCA certified for air performance on direct drive fans

Available in direct driven and belt driven configurations

Impeller type: Adjustable pitch (at rest) cast aluminum

Compact, low cost, high efficiency, rugged design

Available in twenty-one basic fan sizes

Smoke exhaust applications

Customized options available



Evase JMG fans

Volumes to 150,000 CFM	Volumes
Pressures to 10.5" WG	Pressure
Available in direct driven configuration only	Available
Impeller type: Adjustable pitch (at rest) cast aluminum	Impeller controlla
Saves energy and space by incorporating a built-in outlet cone	Significa mainten
Available in eleven basic fan sizes	Available
Customized options available	Custom



Volumes to 400,000 CFM
Pressures to 13" WG
Available in direct driven configuration only
Impeller type: Adjustable pitch (at rest) or controllable pitch (in motion) cast aluminum
Significant power savings, reliable and low maintenance
Available in thirteen basic fan sizes
Customized options available



Mixed flow "plus" fans

Volumes to 65,000 CFM
Pressures to 7" WG
Available in belt driven configuration only
Impeller type: Hybrid, welded steel
Compact, quiet and efficient
Available in eleven basic fan sizes
Customized options available

Howden exceeds customer requirements with specially designed and configured products.





At the heart of your operations

Howden people live to improve our products and services and for over 160 years our world has revolved around our customers. This dedication means our air and gas handling equipment adds maximum value to your operations. We have innovation in our hearts and every day we focus on providing you with the best solutions for your vital operations.



Revolving Around You[™]

©Howden Group Limited. All rights reserved. 2015. Howden and the flying H logo are registered trade marks belonging to Howden Group Limited.