

FSC-MAX FLUID



FSCURTIS

Engineered Lubricants

FSC-Max Fluid is designed to offer the highest protection for your FS-Curtis products. FS-Curtis offers some of the most comprehensive warranty packages in the industry and only FSC-Max Fluid can ensure you are covered.

Protect your warranty coverage and your investment with FSC- Max Fluids.



FSC-Max Fluid ST

ST is our core reciprocating fluid. Used for our factory fill, all FS-Curtis reciprocating units are shipped fully charged with FSC-Max Fluid ST. The ST will protect your reciprocating compressor when you need it most. Viscosity 68

FSC-Max Fluid ET

ET is designed for elevated temperatures. Used in areas of the world that can experience hot, humid and arid temperatures. FSC-Max Fluid ET is rated at 100% fluid life at 212°F (100°C). Viscosity 100

FSC-Max Fluid HP

HP is a Diester –Based synthetic formula. Used in the FS-Curtis CW series for Large Industrial reciprocating air compressors. Formulated to perform above 200 PSI. Viscosity 100

FSC-Max Fluid FS

FS is our core rotary screw fluid. Used for our factory fill, all FS-Curtis rotary screw units are shipped fully charged with FSC-Max Fluid FS. The FS is formulated to perform as a full synthetic PAO fluid. Viscosity 46

FSC-Max Fluid FG

FG is designed for rotary screw food grade applications. The FSC-Max Fluid FG is H1 compliant to cover your most demanding installations.